

Uni Tube Cable CST Armoured




KABELOVNA Děčín Podmokly s.r.o.
 Ústecká 840/33, 405 33 Děčín 5
 Czech Republic
 DIČ CZ26759993
 tel.: +420 412 706 222
 www.kabelovna.cz

ID: **BHOI**

25. 5. 2021 ver. 7

A-DQ(BN)B(SR)2Y max. 24F

This cable is suitable for outdoor installation and classic choice will be better „direct burial possible“.



Mechanical and Environmental properties

Test	Value	Unit	Method
Cable outer diameter	9,9±0,5	mm	EN 60811-203
Cable weight	98	kg/km	
Outer jacket thickness	1,2	mm	
Loose tube diameter	3	mm	
Max. tensile strength	2500	N	EN 60794-1-21-E1
Crush resistance test	6000	N	EN 60794-1-21-E3
Impact resistance test	40	Nm	EN 60794-1-21-E4
Min. bend radius (no load)	15	× OD	EN 60794-1-21-E11a
Min. bend radius (load)	20	× OD	EN 60794-1-21-E11b
Temperature range	Installation	-15 to +50	°C
	Operation	-20 to +70	°C
	Storage	-20 to +70	°C

Cable life time - minimum 30 years

Sheat Marking

Print colour	White
Print method	INK-Jet or Hot-foil
Print legend	Manufacturer's name, job number, type of cable, length marking @ 1 m intervals

Other print legends available on request

Fibre colour coding

According to IEC 60304

1	Red	7	Brown	13	Red*	19	Brown*
2	Green	8	Violet	14	Green*	20	Violet*
3	Blue	9	Turquoise	15	Blue*	21	Turquoise*
4	Yellow	10	Black	16	Yellow*	22	Natur*
5	White	11	Orange	17	White*	23	Orange*
6	Grey	12	Pink	18	Grey*	24	Pink*

*with black rings

Other fibre colour sequences available on request

Packing

Depending on ordered put-up lengths

